

# **Models of Acoustic Wave Scattering at 0.2-10 kHz from Turbulence in Shallow Water**

Tokuo Yamamoto

Division of Applied Marine Physics, RSMAS, University of Miami,  
4600 Rickenbacker Causeway Miami, FL 33149

phone: (305) 421-4637 fax: (305) 421-4701 email: [tyamamoto@rsmas.miami.edu](mailto:tyamamoto@rsmas.miami.edu)

Award Number: N000140810322

## **LONG-TERM GOALS**

Long term goals are to better understand the physics of acoustic wave propagation in turbulence. Long-term goals are to develop mathematical model of acoustic wave scattering in turbulence, observe acoustic wave scattering (attenuation) in turbulence, and compare model with observation. This scheme is also extended to internal wave. All the mechanisms involved in the process of scattering and attenuation will be observed and compared with theory.

## **OBJECTIVES**

The scientific and technological objectives are to develop a shallow ocean model assimilated with acoustic data. Also other objectives are to develop acoustic tomography to image the current velocity and turbulence in 3D space. The other objectives are to image acoustic wave scattering and attenuation. The objectives are to apply the numerical inverse methods to locate the trace of a submarine, manned and unmanned submersibles, and torpedo.

## **APPROACH**

1. Develop shallow ocean model with data assimilation of tide gages, and acoustic data in real time.[Data assimilation model to be built as fund become available.]
2. Develop theoretical and numerical models of acoustic wave propagation in turbulent current.
3. Extract the turbulent structure from the archived (Kanmon Strait) data of average current and free stream turbulence inversely using the theoretical and numerical models of (2). The complete Kanmon Strait data were presented to the author by Dr. Arata Kaneko.
4. Compare the turbulent structure determined from data with the theoretical prediction.
5. Extract the acoustic wave attenuation and scattering from the Kanmon Strait data using tomography technique.
6. Repeat step 1 to 5 for internal wave when the tasks for turbulence will have been finished.

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 2008</b>		2. REPORT TYPE <b>Annual</b>		3. DATES COVERED <b>00-00-2008 to 00-00-2008</b>	
4. TITLE AND SUBTITLE <b>Models Of Acoustic Wave Scattering At 0.2-10 kHz From Turbulence In Shallow Water</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>University of Miami,Division of Applied Marine Physics, RSMAS,4600 Rickenbacker Causeway,Miami,FL,33149</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>code 1 only</b>					
14. ABSTRACT <b>Long term goals are to better understand the physics of acoustic wave propagation in turbulence. Long-term goals are to develop mathematical model of acoustic wave scattering in turbulence, observe acoustic wave scattering (attenuation) in turbulence, and compare model with observation. This scheme is also extended to internal wave. All the mechanisms involved in the process of scattering and attenuation will be observed and compared with theory.</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>6</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

7. Dr. Yamamoto will take over all tasks 1 to 5. Dr. Mohsen Badiy will supply his tomography data to PI. Also, Robert Field of NRL-SSC will provide his acoustic wave transmission data through turbulence and internal wave. The PI and Altan Turgut will collaborate in the work of Ship noise propagation. The PI's analytical wave turbulence interaction will be used on Turgut data for the influence of turbulence on the Noise propagation. The experimental data will be compared with the theoretical and numerical models of acoustic wave propagation through turbulence.

## **WORK COMPLETED**

### **Model of Acoustic Wave Propagation, Scattering and Attenuation in Turbulence**

An analytical solution for acoustic wave scattering in turbulence (or internal wave) was derived.

### **Accurate Prediction of Oceanography by Data Assimilation [for Data Assimilation funding are being requested]**

The locations of eight acoustic source-receiver pairs are given by solid dots in Figure 1. The number of acoustic pair starts from the west end on the north shore and turn clockwise. The area of tomography coverage is 1500 m wide x 2500 m. Three predictions of current field are compared in Figure 1. The red arrows are from ADCP. The black arrows are from acoustic tomography. White arrows are prediction by Princeton Ocean Model (POM) with kalman filter assimilation with a tide gage and selected acoustic transmission data from tomography rays. The assimilated POM is the most accurate.

At this phase of tidal current, the maximum current ( $\sim 4$  m/s) runs against the Northern shore while flow separation and a large counter clockwise eddy ( $\sim 1$  m/s) occupies the space between the midway and Southern shore. It is observed that acoustic wave attenuate below noise level when it travel (K1 to K5) through a high velocity current ( $\sim 4$  m/s) as shown in Figure 2. Attenuation is small for acoustic wave propagates through a large eddy (K8 to K5) with low current velocity ( $\sim 1$  m/s) as shown in Figure 3. These experimental facts are all predicted well by the theoretical model.

It is accomplished that the tidal current produces free stream turbulence proportional to the square of current velocity in shallow waters like Kanmon Strait. Where there is a high current there is strong turbulence and acoustic wave scatter off its energy strongly and attenuate strongly. On the other hand, where there is a low current, there is low turbulence energy. Acoustic wave hardly scatters its energy and propagates without losing energy much.

## **IMPACT/APPLICATIONS**

Theoretical means to accurately predict the behavior of free stream turbulence has been established and being validated by At Sea experiment. This method can be applied to locate submarine after careful submarine location experiments will have been done to verify the theoretical models.

## **TRANSITIONS**

A potential future transition applies to the theoretical model to determine the behavior of free stream turbulence leading to location of submarines.

## **RELATED PROJECTS**

Mohsen Badiey, Acoustic tomography using vector sensors.

Robert Fields, Acoustic wave propagation in Shallow Waters.

Altan Tugut, Use of ship noise for characterizing bottom sediments.

## **REFERENCES**

Ishimaru, Akira, Wave propagation and scattering in Random Media, Volume 1 and 2; Academic Press, Inc. New York, NY 1978.

Tatarski, Victor, Wave Propagation in a Turbulent Medium: McGraw-Hill Book Company, Inc. English Translation 1961

## **PUBLICATIONS**

Yamamoto, T and Yamaoka, H, Acoustical Observations of Internal Wave Evolutions in New York Continental Margin: IEEE Oceanographic Engineering, [Being Reviewed]

Badiey, M., and Yamamoto, T., High-frequency acoustic current tomography in shallow water; Journal of Acoustical Society of America [Under Review].


Turgut, A. and Yamamoto, T., In-Situ Measurements of Velocity Dispersion and Attenuation in New Jersey Shelf Sediments: Journal of Acoustical Society of America, Extended Abstract [IN PRESS]

Sakakibara, J. and Yamamoto, T., Development of High Resolution Measurement Method of Earth Structure Using High Frequency Acoustic Wave: Japan Society of Civil Engineers Journal of Geotechnical Engineering [Under Review].


Badiey, M., and Yamamoto, T., High-frequency acoustic current tomography in shallow water; Journal of Acoustical Society of America [Being Reviewed].

Turgut, A. and Yamamoto, T., In-Situ Measurements of Velocity Dispersion and Attenuation in New Jersey Shelf Sediments: Journal of Acoustical Society of America, Extended Abstract [IN PRESS]


Sakakibara, J. and Yamamoto, T., Development of High Resolution Measurement Method of Earth Structure Using High Frequency Acoustic Wave: Japan Society of Civil Engineers Journal of Geotechnical Engineering [Under Review].



***Figure 1. The red arrows are from ADCP. The black arrows are from acoustic tomography. White arrows are prediction by Princeton Ocean Model (POM) with kalman filter assimilation with a tide gage and selected acoustic transmission data.***



***Figure 2. Received correlation wave form. M-sequence length is 1023. Signal propagates from station K1 to K5 range 2300 m. K1-K5 path goes through a very strong tidal current. Due to the strong current ( $\sim 4$  m/s), strong turbulence is generated. Thus, acoustic wave scatter strongly and attenuate strongly. Signal is buried under noise and can not be detected.***



***Figure 3. Received Correlation Wave Form for 1023 digits M sequence signal for signal transmission from K8 to K5, 2300 m. As can be seen in Figure 1, the path K8-K5 is in the slowly moving eddy ( $\sim 1$  m/s). This is why K8-K5 has very high  $S/N = 18$ . The analytical model predicts this very well.***